

## VIBRATORY TAMPERS

The Tremix Tampers are machines with low exhaust emissions and low noise with high compaction performance.

- Used for compaction of granular and cohesive soils.
- Most suitable for compaction in confined areas, trenches and repair work.
- High working speed.
- High amplitude vibrations effective up to 60cm depth for sand gravel and 15 - 20cm on clay.
- Low hand/arm vibration.
- Conveniently located throttle control.
- Low maintenance cost.



TAMPERS TECHNICAL DATA		
	MS 620	MS 680
Net Weight,	63 kg.	73 kg.
Operating weight	64 kg.	74 kg.
Frequency	12 Hz.	12 Hz.
Amplitude (jumping height)	65 - 75 mm.	65 - 75 mm.
Working speed	15 - 18 m/min	15 - 18 m/min.
<b>Engine</b>		
Brand	Honda 4 stroke	Honda 4-stroke
Model	GX 100	GX 120
Starting system	Recoil	Recoil
Fuel	Petrol	Petrol
Output	2.2/3600 kw/rpm.	2.9/3600 kw/rpm.
Fuel tank capacity	2.5 Liter	2.5 Liter
Fuel consumption	0.7 Liter / hr.	0.9 Liter / hr.
<b>Dimensions</b>		
Plate W x L	230x330 mm.	280x330 mm.
Overall L x W x H	810x422x1074 mm.	810x422x1074 mm.